



330 Smith St, P.O. Box 70, Arthur ON, N0G 1A0 Canada 1-800-865-7366
info@pros-pick.com or www.pros-pick.com

Aluminum Gas Cap/Pop-Top Fuel Filler Instructions revised April 17, 2007

Thank you for purchasing our Pop-Top Fuel filler. It has been designed with care to give you maximum usability and enjoyment. To open, depress center cap and turn counter clockwise 1/3 of a turn.

Required Tools

2" hole saw, 1 3/4" fuel rated hose, hose clamps, appropriate screw driver

Select a suitable location for the cap, be careful to ensure that there is enough room behind to allow for the hose to bend if necessary. When we buy tanks for our own vehicles, we always buy them with the fill tube supplied but not installed. We then position the cap where we want it and then cut the fill tube into the tank where we need it.

Drill a 2" hole for the cap, insert cap into hole and install lock ring from the rear. Cut and fit fuel hose and clamp securely.

When the unit is installed the final time, using a tooth pick, apply **1** very small dab of clear silicone to the joint between the lock ring and the threads. This will ensure the lock ring does not vibrate loose.

If you require the cap to be vented, drill a 1/8" hole in the center of the plastic piece.

You may find the cap scratches from your fingers. We really like Purple Metal Polish. It is available through Pro's Pick or California Custom Products. We sincerely hope you love this gas cap as much as we do.

